UV DTF STICKER

PRODUCT SPECIFICATION

Material Type	Delivery Sheet Size	Print Size	Print Side & Print Color	Optional Finishing	Quantity (sheets)	Process Days (excluding order day & receive day)
UV DTF Sticker	- A3 (297mm x 420mm) - A4 (210mm x 297mm) - A5 (148mm x 210mm)	- 267mm x 390mm - 180mm x 267mm - 118mm x 180mm	4C (1 Side)	None	1 45 2 50 3 55 4 60 5 65 6 70 7 75 8 80 9 85 10 90 15 95 20 100 25 200 30 300 35 40	Normal Order 2 days (1 - 50 sheets) 3 days (55 - 100 sheets) 5 days (200 - 300 sheets) Cut Off Time: 1pm

Note:

*Artwork with background will be printed.

Precautions:

- Clean the surface of substrate from oil, moisture and dirt before applying.
- To remove sticker, peel off liners instead of facestocks.
- Keep the label in room temperature and avoid direct exposure to sunlight for better durability.
- Do not apply for food contact usage.

CONDITION OF USAGE

PRODUCT SPECIFICATION

Material	UV DTF Sticker	
Application	Normal usage, Dry surface, Indoor purpose, Waterproof	
Any Size or Shape	✓	
Adhesive	Permanent (non-removable)	
Optional Finishing	-	
Tear Resistance	×	
Print Color	CMYK	
Finish and Stock Color	Transparent	

Adhesion between Sticker and Substrate Material

Material	UV DTF Sticker	
	Flat Surface	Curve Surface
High Surface Energy Plastic - PET and PVC	✓	✓
Low Surface Energy Plastic – LDPE , PP and PS	✓	✓
Glass	✓	✓
Coarse Glass / Coarse Plastic	×	×
Ceramic	✓	# 🗸
Metal	✓	# 🗸
Leather	#~	# 🗸
Wood	√	#~
Paper Board / Corrugated Board	✓	# 🗸

Resin Identification Code

PET	Z13 PET
PVC	L23 HDPE
LDPE	<u>د</u> ئے،
PP	253 PP
PS	65 PS

Note: For [#]

✓ might having minor curl issue after long run. Need to test it out.

Resin Identification Code is the standard code indicate in the material surface to identified material type.

¹⁾ This is only a guideline for consumer. Final application is subjected to consumer handling method.
2) The finish and stock color refer to the nature of material surface.